

| Product quality | | Tolerances (EN 13329) | | |
|---|--|---|--|---------------------|
| Formats | 858 x 143 x 8 mm | Squareness of the elements (≤ 0.50 mm) | ≤ 0,10mm | |
| Packaging | Pack: 13 elements / 1.595 m ² / 12.13 kg | Determination of Linearity (≤ 0.30 mm) | ≤ 0,10 mm/m | |
| | Pallet: 56 packs / 89.32 m ² / 694.32 kg | Block alignment | ± 2 mm | |
| Guarantee (according Parador guarantee conditions) | Domestic area | Surface flushness | (average ≤ 0.15 mm) | (average ≤ 0.05 mm) |
| | Commercial area | | (max. ≤ 0.15 mm) | (max. ≤ 0.10 mm) |
| Notes | Lifetime 10 years - not suitable for all-over adhesion - min. compressive strength of underlay (CS) ≥ 120 kPa (e.g. Akustik-Protect) - cleaning and maintenance see instructions - technical changes reserved | Opening between installed elements | (average ≤ 0.15 mm) | (average ≤ 0.05 mm) |
| | | Flatness of elements | fw, concave ≤ 0,15 % fw, convex ≤ 0,20 % | |
| | | | fl, concave ≤ 0,50 % fl, convex ≤ 1,00 % | |



| Classification | | |
|--|--------------------|---|
| | Test method | Rating |
| Utility class 23 domestic areas with intensive use | EN 13329 | Living room, hall, kitchen, home office |
| Utility class 32 commercial areas with medium use | EN 13329 | Classrooms, small offices, shops |
| Abrasion | EN 13329, Annex E | AC 4 (≥ 4.000 rev.) |
| Impact resistance (small ball) | EN 17368 | ≥ 35mm |
| Impact resistance (big ball) | EN 13329, Annex H | ≥ 750mm |
| Reaction to fire | EN 13501-1 | C _f s1 |
| Slip resistance | EN 13893 | μ ≥ 0,35 |
| | EN 14041 | DS |
| Staining resistance | EN 438-2 | Category 1+2: level 5 |
| | | Category 3: level 4/5 |
| Cigarette resistance | EN 438-2 | level 4 |
| Light fastness | EN ISO 4892-2 | Grey scale: Stage ≥ 4 |
| Resistance to roller castor chairs | EN 425 | Type W, no visible changes |
| Electrical behaviour | EN 1815 | ≤ 2 kV |
| Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier. | EN 12664 | 0,048 m ² *K/W |
| Moving a furniture leg | EN ISO 16581 | Type 0, no visible changes |
| Indentation-residual | ISO 24343-1 | ≤ 0,05mm |
| E1 Formaldehyde emission (E1 = 0.1 ppm) | EN 16516 | ≤ 0,05 ppm |
| Locking strength of mechanically assembled panels | ISO 24334 | > 1 kN/m (long side) * kN/m (short side)* not reportable due to construction |
| Acoustical - Impact noise reduction | ISO 717-2 | 14 dB (on Akustik-Protect 100) |
| Dimensional stability | EN 13329, Annex C | ≤ 0,9mm |
| Thickness swelling | ISO 24336 (≤ 18 %) | ≤ 12 % |
| Surface soundness | EN 13329, Annex D | ≥ 1,8 N/mm ² |
| Scratch resistance | EN 438 | Level 4 |
| Slip resistance on an inclined plane | DIN 51130 | Rustique texture: - / Other: R9 |
| Disposal | | EAK-Code-number 20 01 38 |
| Damp room suitability: "The water-resistant product structure enables use in damp rooms (with up to 1h protection against standing water. Please observe installation instructions). | | |

| | | | |
|--|-------------|-------------------|--|
| Changed: | QMB Parador | File: | PA_TDS_Laminat_Trendtime-3_EN_20211101 |
| Date: | 01.01.2014 | Latest update at: | www.parador.eu/service/catalogues-downloads/technical-data-sheets |
| Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from: | | | 01.11.2021 |