

SUMMIT

DECLARATION OF PERFORMANCE

IN ACCORDANCE WITH CONSTRUCTION PRODUCTS REGULATION (EU) NO. 305/2011 DOP 24004A

- 1. Unique identification code of the product-type: Pre-lacquered veneered wooden floor covering with surface coating (groups below) / EN 14342 - EN 14354
- 2. Type, batch or serial number or any other element allowing identification of the construction product: Parky Summit
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: The products are intended for use as floor coverings(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 14342
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): Decospan N.V., Lageweg 33, B-8930 Menen, Belgium. Produced at same location.
- 5. Name and contact address of the authorised representative: Not applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product: AVCP 3 (of Appendix ZA.2 of EN 14342 : 2013)
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard. Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports.
 - Determination of reaction to fire according (EN 13501-1):
 - Centexbel: NB0493, Technologiepark 70, 9052 Gent Belgium, Test reports 20.06759.01 and 20.06759.02
 - Determination of formaldehyde emissions according (EN 16516):
 - Eurofins product testing A/S, Smedeskovvej 38, 8464 Galten Denmark, Test reports 392-2023-00570801_A_EN
 - Determination of the slip resistance:
 - Wood.be, Hof ter Vleestdreef 3, 1070 Anderlecht Belgium, Test report 200034/1
 - Determination of the thermal conductivity (EN 12667):
 - Wood.be, Hof ter Vleestdreef 3, 1070 Anderlecht Belgium, Test reports 180646/6; 180646/4
- 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable
- 9. Declared performance: EN14342: 2013 Wood Flooring

Product	PARKY SUMMIT
Mean Density	850 kg/m³
Total Thickess	10 mm
Backing	Veneer
Reaction to fire (EN13501-1)	Class Cfl-s1
Formaldehyde Emission (EN 717-1)	Class E1
Content PCP (EN 14342)	<5 ppm
Slip resistance (CEN/TS 15676)	≥45 USRV
Thermal conductivity (EN 12667)	0.14 W/m*K
Biological durability (EN 335)	Class 1
Dimensions	2050×233×10 mm
Installation method	Floating installation

Pieterjan Desmet